

Price Schedule

Name of Work: Aluminum & wall partition work at ground floor production engineering building at NIT Silchar.

Size of aluminum partition - 5.45 x 3.00 & Pre-laminated wall partition - 7.30 x 3.00M

Completion period: 15 days.

OR:
CR:
OM:

Sl. No.	Description of Item	Unit	Quantity	Rate in word	Rate in Fig	Amount
1	Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	Each	1.00			
2	Providing and fixing aluminium sliding door bolts ISI marked anodized (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with nuts and screws etc.,complete: 300 x 16 mm. Coloured.	Each	2.00			
3	Providing and fixing aluminium tower bolts ISI marked anodized (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with nuts and screws etc.,complete. 300 x 10 mm. Coloured.	Each	2.00			
4	Providing and fixing aluminium hanging floor door stopper ISI marked anodized (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with nuts and screws etc.,complete: Twin rubber stopper. Coloured.	Each	2.00			

Sl. No.	Description of Item	Unit	Quantity	Rate in word	Rate in Fig	Amount
5	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections / appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required EPDM rubber / neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all compete as per architectural drawings and directions of Engineer – in – charge. (Glazing and paneling to be paid for separately): For fixed portion - Powder coated aluminium (minimum thickness of powder coating of 50 micron). Coloured	Kg	150.00			

Sl. No.	Description of Item	Unit	Quantity	Rate in word	Rate in Fig	Amount
6	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections / appropriate Z sections and other sections of approved make conforming to IS : 733 and IS: 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required EPDM rubber / neoprene gasket etc., Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and directions of Engineer – in – charge. (Glazing and paneling to be paid for separately): For shutters of doors, windows & ventilators including providing and fixing hinges / pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately). Powder coated aluminium (minimum thickness of powder coating of 50 micron). coloured	Kg	35.00			
7	Providing and fixing 12 mm thick pre-laminated particle board flat pressed three layer or graded wood particle board conforming to IS : 12823 Grade I Type II, in paneling fixed in aluminium doors, windows shutter and partitions frames with C.P. brass / stainless steel screws etc., complete as per architectural drawings and directions of Engineer - in – Charge. Pre-laminated particle board with decorative lamination on both sides	Sqm	12.00			

Sl. No.	Description of Item	Unit	Quantity	Rate in word	Rate in Fig	Amount
8	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc., with EPDM rubber / neoprene gasket etc., complete as per the architectural drawings and the directions of Engineer – in – charge. (Cost of aluminium snap beading shall be paid in basic item) : With float glass panes of 5.50 mm thickness.	Sqm	8.00			
9	Filling the gap in between aluminium frame & adjacent RCC/Brick/Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete. Upto 5mm depth and 5 mm width	Rmt	12.00			
10	Providing and fixing aluminium tubular handle bar 32 mm outer dia, 3.0 mm thick & 2100 mm long with SS screws etc .complete as per direction of Engineer-in-Charge. Powder coated minimum thickness 50 micron aluminium tubular handle bar	Each	2.00			
11	Providing and fixing double action hydraulic floor spring of approved brand and manufacture conforming to IS : 6315, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 125 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer box with slide plate etc. complete as per the direction of Engineer-in-charge. With stainless steel cover plate minimum 1.25 mm thickness	Each	1.00			
12	Providing wood work in frames of false ceiling, partitions etc. sawn and fixed in position : Sal wood	Cum	0.25			

Sl. No.	Description of Item	Unit	Quantity	Rate in word	Rate in Fig	Amount
13	Providing and fixing Pre -laminated medium density fibre board exterior grade (Grade-I) IS:14587:1998 marked, to frame, backing or studding with screws etc. complete (Frames, backing or studding to be paid separately). Pre-laminated with decorative lamination on both side exterior Grade - I MDF Board 12 mm thick conforming to IS:14587	Sqm	21.90			
14	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters: 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	Sqm	2.10			
15	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work	Sqm	10.04			
16	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. 25 mm nominal outer dia Pipes	Rmt	24.00			

Sl. No.	Description of Item	Unit	Quantity	Rate in word	Rate in Fig	Amount
17	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. 20 mm nominal outer dia Pipes	Rmt	12.00			
18	Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 : 15 mm nominal bore	Each	1.00			
19	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete : 25 mm nominal bore	Each	2.00			

Total = Rs.

Rupees

Signature of the Agency